

ORDERING INFORMATION CONTINUED

Standard 2 hp Fixed Speed Submersible Turbine Pumps

| Model | Description | Model Length Range Number | Model Length Range* |
|--------------|---|---------------------------|---------------------|
| STPM200-VL1 | 2 hp fixed speed with MagShell® | VL1 | 63" - 91" |
| STPM200-VL2 | 2 hp fixed speed with MagShell® | VL2 | 94" - 154" |
| STPM200-VL3 | 2 hp fixed speed with MagShell® | VL3 | 126" - 217" |
| STPHM200-VL1 | 2 hp high pressure fixed speed with MagShell® | VL1 | 63" - 92" |
| STPHM200-VL2 | 2 hp high pressure fixed speed with MagShell® | VL2 | 94" - 155" |
| STPHM200-VL3 | 2 hp high pressure fixed speed with MagShell® | VL3 | 126" - 218" |

Alcohol-Gas (AG) 2 hp Fixed Speed Submersible Turbine Pumps

| Model | Description | Model Length Range Number | Model Length Range* |
|----------------|--|---------------------------|---------------------|
| STPAGM200-VL1 | 2 hp AG fixed speed with MagShell® | VL1 | 63" - 91" |
| STPAGM200-VL2 | 2 hp AG fixed speed with MagShell® | VL2 | 94" - 154" |
| STPAGM200-VL3 | 2 hp AG fixed speed with MagShell® | VL3 | 126" - 217" |
| STPAGHM200-VL1 | 2 hp AG high pressure fixed speed with MagShell® | VL1 | 63" - 92" |
| STPAGHM200-VL2 | 2 hp AG high pressure fixed speed with MagShell® | VL2 | 94" - 155" |
| STPAGHM200-VL3 | 2 hp AG high pressure fixed speed with MagShell® | VL3 | 126" - 218" |

Notes:

1. Remove "M" from model number for non-MagShell® pump motor assembly.
2. STP models are compatible with fuel mixtures containing up to 10% ethanol with gasoline, up to 5% Biodiesel with diesel fuels, and 20% MTBE, 20% ETBE or 17% TAME with gasoline. STPAG models are compatible with fuel mixtures containing diesel fuel with up to 20% Biodiesel, 100% Biodiesel, up to 85% ethanol with gasoline, and 20% MTBE, 20% ETBE or 17% TAME with gasoline.
3. All models are supplied with a standard check valve unless factory option "R" or "W" is specified.
4. All above models require single-phase, 208-230 VAC, 60 Hz incoming power.
5. 4" riser pipe, if supplied locally, must be 4½" OD by 3/16" WT tubing.
6. For riser pipe lengths 31" to 60", additional charges apply (call Customer Service for lead times).

*Model length (A) defined as the dimension from turbine manifold bottom to pump motor inlet.

Factory Installed Options

Specified in model number at time of STP order.

| Model | Description |
|-------|--|
| F | Floating suction adapter, 1½" NPT female, must be factory installed |
| K | IFS (intake filter screen) factory assembled to pump motor assembly |
| R | Model R check valve, factory installed, for Veeder-Root® PLLD Line Leak |
| W | Model W check valve, factory installed, for Red Jacket PPM4000 Line Leak |

Field Installed Options

2 hp fixed speed specific accessories.

| Model | Description |
|------------|---|
| 400137908 | Syphon check valve, alcohol-gasoline compatible (when ordered with STP) |
| 400818921 | STP-CBS, single-phase control box with lockout switch, 120 Volt coil |
| 402312921 | STP-DHI-SCI, combo DHI with factory-wired STP-SCI |
| 402313921 | STP-DHI-CBS, combo DHI with factory-wired STP-CBS |
| 402459931 | Model 65 psi check valve AG compatible, (for slave of manifolded STPs with Veeder-Root® PLLD) |
| 402507930 | Secondary syphon kit (when two syphon primes are required for one STP) |
| 5800100215 | STP-SCI, single-phase Smart Controller |
| 5800300100 | STP-DHI, dispenser hook isolation for 120 Volt dispenser handle switches, up to eight each |