FR1210HA



FR1210HA1



FR1210HA1F



DESCRIPTION	Gasoline Automatic Nozzle	Diesel Automatic Nozzle	Diesel Automatic Nozzle, Filter
FLOW RATE	15 GPM / 57 LPM	15 GPM / 57 LPM	15 GPM / 57 LPM
VOLTAGE / AMP RATING (FLA)	12V DC / 20 A	12V DC / 20 A	12V DC / 20 A
DUTY CYCLE	30 min on / 30 min off	30 min on / 30 min off	30 min on / 30 min off
DISCHARGE HEAD / DISCHARGE PRESSURE	37' / 16 PSI	37' / 16 PSI	37' / 16 PSI
SUCTION LIFT	8'	8'	8'
INLET THREAD / OUTLET THREAD	1" NPT / 0.75" NPT	1" NPT / 0.75" NPT	1" NPT / 0.75" NPT
MOUNTING SIZE, THREAD, TYPE	2" NPT Bung Mount	2" NPT Bung Mount	2" NPT Bung Mount
KEY INCLUDED COMPONENTS	34" x 12' Hose with Static Ground Wire, 34" Automatic Unleaded Nozzle, 20" – 34-1/2" Steel Telescoping Suction Pipe, 2-Wire 12 GA 18' Power Cable	34" x 12' Hose with Static Ground Wire, 34" Automatic Diesel Nozzle, 20" – 34-½" Steel Telescoping Suction Pipe, 2-Wire 12 GA 18' Power Cable	10 Micron Particulate Filter and Filter Head, ¾" x 12' Hose with Static Ground Wire, ¾" Automatic Diesel Nozzle, 20" – 34-½" Steel Telescoping Suction Pipe, 2-Wire 12 GA 18' Power Cable
COMPATIBLE FLUIDS	DG K B20E15MS	DG K B20E15MS	DG K B20E15MS
PACKAGE DIMENSIONS (WxHxD) / WEIGHT	15.44" x 10.63" x 18.31" / 32 lbs	15.44" x 10.63" x 18.31" / 33 lbs	15.44" x 10.63" x 18.31" / 39 lbs
CERTIFICATIONS	cULus	cULus	cULus
WARRANTY	Limited Lifetime	Limited Lifetime	Limited Lifetime
UPC	089404247938	089404248003	089404249901