

FR1211HLN



FR1211HL



FR1211HEL



FR1211HELA



DESCRIPTION	Mechanical Meter (Liters)	Mechanical Meter (Liters), Manual Nozzle	ATEX Motor, Mechanical Meter (Liters), Manual Nozzle	ATEX Motor, Mechanical Meter (Liters), Gasoline Automatic Nozzle
FLOW RATE	57 LPM	57 LPM	57 LPM	57 LPM
VOLTAGE / AMP RATING (FLA)	12V DC / 20 A	12V DC / 20 A	12V DC / 20 A	12V DC / 20 A
DUTY CYCLE	30 min on / 30 min off	30 min on / 30 min off	30 min on / 30 min off	30 min on / 30 min off
DISCHARGE HEAD / DISCHARGE PRESSURE	37' / 16 PSI	37' / 16 PSI	37' / 16 PSI	37' / 16 PSI
SUCTION LIFT	8'	8'	8'	8'
INLET THREAD / OUTLET THREAD	1" NPT / 0.75" NPT	1" NPT / 0.75" NPT	1" NPT / 0.75" NPT	1" NPT / 0.75" NPT
MOUNTING SIZE, THREAD, TYPE	2" NPT Bung Mount	2" NPT Bung Mount	2" NPT Bung Mount	2" NPT Bung Mount
KEY INCLUDED COMPONENTS	807CL Mechanical Meter (Liters), 20" – 34-½" Steel Telescoping Suction Pipe, 2-Wire 12 GA 18' Power Cable	807CL Mechanical Meter (Liters), ¾" x 12' Hose with Static Ground Wire, ¾" Cast Aluminum Manual Nozzle, 20" – 34-½" Steel Telescoping Suction Pipe, 2-Wire 12 GA 18' Power Cable	807CL Mechanical Meter (Liters), ¾" x 12' Hose with Static Ground Wire, ¾" Cast Aluminum Manual Nozzle, 20" – 34-½" Steel Telescoping Suction Pipe, 3-Wire 12 GA 18' Power Cable	807CL Mechanical Meter (Liters), ¾" x 12' Hose with Static Ground Wire, ¾" Automatic Unleaded Nozzle, 20" – 34-½" Steel Telescoping Suction Pipe, 3-Wire 12 GA 18' Power Cable
ACCURACY	+/- 1%	+/- 1%	+/- 1%	+/- 1%
COMPATIBLE FLUIDS				
PACKAGE DIMENSIONS (WxHxD) / WEIGHT	21.81" x 10" x 19.81" / 33 lbs	21.81" x 10" x 19.81" / 37 lbs	21.81" x 10" x 19.81" / 39 lbs	21.81" x 10" x 19.81" / 37 lbs
CERTIFICATIONS	cULus	cULus	ATEX, CE, IECEx, INMETRO	ATEX, CE, IECEx, INMETRO
WARRANTY	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime
UPC	089404248102	089404248096	089404248072	089404248089

DC PUMPS

AC PUMPS

NEXT-EC

HAND PUMPS

METERS

CABINET DISPENSERS

FMS

ACCESSORIES

DEF

KITS