

FR4204H






FR4210HN



FR4210H



DESCRIPTION	Pump Only	Suction Pipe Only	Manual Nozzle
FLOW RATE	20 GPM / 75 LPM	20 GPM / 75 LPM	20 GPM / 75 LPM
VOLTAGE / AMP RATING (FLA)	12V DC / 19 A	12V DC / 19 A	12V DC / 19 A
DUTY CYCLE	30 min on / 30 min off	30 min on / 30 min off	30 min on / 30 min off
DISCHARGE HEAD / DISCHARGE PRESSURE	37' / 16 PSI	37' / 16 PSI	37' / 16 PSI
SUCTION LIFT	8'	8'	8'
INLET THREAD / OUTLET THREAD	1" NPT / 1" NPT	1" NPT / 1" NPT	1" NPT / 1" NPT
MOUNTING SIZE, THREAD, & TYPE	2" NPT Bung Mount	2" NPT Bung Mount	2" NPT Bung Mount
KEY INCLUDED COMPONENTS		20" – 34-½" Steel Telescoping Suction Pipe, 2-Wire 12 GA 18' Power Cable	1" x 12' Hose with Static Ground Wire, 1" Cast Aluminum Manual Nozzle, 20" – 34-½" Steel Telescoping Suction Pipe, 2-Wire 12 GA 18' Power Cable
COMPATIBLE FLUIDS			
PACKAGE DIMENSIONS (WxHxD) / WEIGHT	12.63" x 6.63" x 15.25" / 22.5 lbs	15.44" x 10.63" x 18.31" / 24.03 lbs	15.44" x 10.63" x 18.31" / 35 lbs
CERTIFICATIONS	cULus	cULus	cULus
WARRANTY	Limited Lifetime	Limited Lifetime	Limited Lifetime
UPC	089404247945	089404248249	089404247952

DC PUMPS

AC PUMPS

NEXTEC

HAND PUMPS

METERS

CABINET DISPENSERS

FMS

ACCESSORIES

DEF

KITS