

FR4211HN



FR4211H



FR4219H



DESCRIPTION	Mechanical Meter (Gallons), Suction Pipe	Mechanical Meter (Gallons), Manual Nozzle	Digital Meter, Manual Nozzle
FLOW RATE	20 GPM	20 GPM	20 GPM / 75 LPM
VOLTAGE / AMP RATING (FLA)	12V DC / 19 A	12V DC / 19 A	12V DC / 19 A
DUTY CYCLE	30 min on / 30 min off	30 min on / 30 min off	30 min on / 30 min off
DISCHARGE HEAD / DISCHARGE PRESSURE	37' / 16 PSI	37' / 16 PSI	37' / 16 PSI
SUCTION LIFT	8'	8'	8'
INLET THREAD / OUTLET THREAD	1" NPT / 1" NPT	1" NPT / 1" NPT	1" NPT / 1" NPT
MOUNTING SIZE, THREAD, & TYPE	2" NPT Bung Mount	2" NPT Bung Mount	2" NPT Bung Mount
KEY INCLUDED COMPONENTS	901C Mechanical Meter (Gallons), 20" – 34-½" Steel Telescoping Suction Pipe, 2-Wire 12 GA 18' Power Cable	901C Mechanical Meter (Gallons), 1" x 12' Hose with Static Ground Wire, 1" Cast Aluminum Manual Nozzle, 20" – 34-½" Steel Telescoping Suction Pipe, 2-Wire 12 GA 18' Power Cable	TT10AN Digital Meter, 1" x 12' Hose with Static Ground Wire, 1" Cast Aluminum Manual Nozzle, 20" – 34-½" Steel Telescoping Suction Pipe, 2-Wire 12 GA 18' Power Cable
ACCURACY	+/- 2%	+/- 2%	+/- 1%
COMPATIBLE FLUIDS			
PACKAGE DIMENSIONS (WxHxD) / WEIGHT	21.81" x 10" x 19.81" / 44.14 lbs	21.81" x 10" x 19.81" / 44.14 lbs	21.81" x 10" x 19.81" / 39 lbs
CERTIFICATIONS	cULus	cULus	cULus
WARRANTY	Limited Lifetime	Limited Lifetime	Limited Lifetime
UPC	089404248287	089404247983	089404248294