

MANUAL NOZZLES

FRHMN075S



FRHMN100S



DC PUMPS		
AC PUMPS		
NEXTEC		
HAND PUMPS		
METERS		
CABINET DISPENSERS		
FMS		
ACCESSORIES		
DEF		
KITTS		
DESCRIPTION	¾" Manual Nozzle	1" Manual Nozzle
MAX FLOW RATE	20 GPM / 75 LPM	40 GPM / 151 LPM
INLET SIZE (ID)	¾" NPT	1" NPT
SPOUT SIZE (OD)	13/16" / 21 mm	15/16" / 24 mm
MAX WORKING PRESSURE	50 PSI / 3.4 bar	50 PSI / 3.4 bar
PRESSURE DROP	3.6 PSI @ 20 GPM	2.9 PSI @ 25 GPM
MINIMUM OPERATION TEMP.	-20°F / -29°C	-20°F / -29°C
INTEGRAL SPOUT SPRING	No	No
AUTOMATIC SHUTOFF	No	No
NUMBER OF LATCH POSITIONS	0	0
NO-PRESSURE, NO-FLOW FUNCTIONALITY	No	No
SEAL MATERIAL	Viton®	Viton®
FLUID COMPATIBILITY		
CERTIFICATIONS	UL/cUL	UL/cUL
WARRANTY	1 Year	1 Year
UPC	089404222669	089404222676