## NX25-120NB-PX



## NX25-120NB-AA



DESCRIPTION	Bung - NPT Threads, Pump Only	Bung - Diesel Automatic Nozzle	Bung - Gasoline Automatic Nozzle
FLOW RATE	25 GPM / 95 LPM	25 GPM / 95 LPM	25 GPM / 95 LPM
VOLTAGE / AMP RATING (FLA)	115V AC / 3.5 A	115V AC / 3.5 A	115V AC / 3.5 A
DUTY CYCLE	Continuous Duty	Continuous Duty	Continuous Duty
DISCHARGE HEAD / DISCHARGE PRESSURE	48' / 25 PSI	48' / 25 PSI	48' / 25 PSI
SUCTION LIFT	12'	12'	12'
INLET THREAD / OUTLET THREAD	1.25" NPT / 1" NPT	1.25" NPT / 1" NPT	1.25" NPT / 1" NPT
MOUNTING SIZE, THREAD, & Type	2" NPT Bung Mount	2" NPT Bung Mount	2" NPT Bung Mount
KEY INCLUDED COMPONENTS		1" x 18' UL Listed Hose with Static Ground Wire, & 1" Ultra High-Flow Automatic Diesel Nozzle (Red)	3/4" x 12' UL Listed Hose with Static Ground Wire, & 3/4" Automatic Unleaded Nozzle
COMPATIBLE FLUIDS	DG K 820 E15 MS	DG K 820 E15 MS	DG K 820 E15 MS
PACKAGE DIMENSIONS (WxHxD) / WEIGHT	15.44" x 11.38" x 18.31" / 29.3 lbs	21.81" x 11.38" x 19.81" / 44 lbs	21.81" x 11.38" x 19.81" / 44 lbs
CERTIFICATIONS	cULus	cULus	cULus
WARRANTY	Limited Lifetime	Limited Lifetime	Limited Lifetime
UPC	089404247471	089404247488	089404248874