NX25-120 SERIES

KITS



NX25-120NB-AB



DESCRIPTION	Bung - Mechanical Meter (Gallons), Diesel Automatic Nozzle	Bung - Digital Meter & Diesel Automatic Nozzle
FLOW RATE	25 GPM	25 GPM / 95 LPM
VOLTAGE RANGE / AMP RATING	115V AC / 3.5 A	115V AC / 3.5 A
DUTY CYCLE (MIN)	Continuous Duty	Continuous Duty
DISCHARGE HEAD / DISCHARGE PRESSURE	48' / 25 PSI	48' / 25 PSI
SUCTION LIFT	12'	12'
INLET THREAD / OUTLET THREAD	1.25" NPT / 1" NPT	1.25" NPT / 1" NPT
MOUNTING SIZE, THREAD, & Type	2" NPT Bung Mount	2" NPT Bung Mount
KEY INCLUDED COMPONENTS	901C Mechanical Meter (Gallons), 1" x 18' UL Listed Hose with Static Ground Wire, & 1" Ultra High-Flow Automatic Diesel Nozzle (Red)	900CD Digital Meter, 1" x 18' UL Listed Hose with Static Ground Wire, & 1" Ultra High-Flow Automatic Diesel Nozzle (Red)
ACCURACY (+/- %)	+/- 2%	+/- 1.25%
REPEATIBILITY (+/- %)	+/- 0.25 %	+/- 0.25 %
COMPATIBLE FLUIDS	DG K B20E15MS	DG K B20E15MS
PACKAGE DIMENSIONS (WxHxD) / WEIGHT	21.81" x 11.38" x 19.81" / 44 lbs	21.81" x 11.38" x 19.81" / 52.3 lbs
CERTIFICATIONS	cULus	cULus
WARRANTY	Limited Lifetime	Limited Lifetime
UPC	089404248898	089404247495