

## RD812BN



## RD1212BN



## RD1212NH



## RD1212NP



	RD812BN	RD1212BN	RD1212NH	RD1212NP
<b>DESCRIPTION</b>	BSPP Threads, Pump Only	BSPP Threads, Pump Only	Suction Hose, Manual Nozzle	Suction Pipe, Manual Nozzle
<b>FLOW RATE</b>	8 GPM / 30 LPM	12 GPM / 45 LPM	12 GPM / 45 LPM	12 GPM / 45 LPM
<b>VOLTAGE / AMP RATING (FLA)</b>	12V DC / 14 A	12V DC / 14 A	12V DC / 14 A	12V DC / 14 A
<b>DUTY CYCLE</b>	30 min on / 30 min off	30 min on / 30 min off	30 min on / 30 min off	30 min on / 30 min off
<b>DISCHARGE HEAD / DISCHARGE PRESSURE</b>	37' / 16 PSI	37' / 16 PSI	37' / 16 PSI	37' / 16 PSI
<b>SUCTION LIFT (FT)</b>	6'	6'	6'	6'
<b>INLET THREAD / OUTLET THREAD</b>	0.75" BSPP / 0.75" BSPP	0.75" BSPP / 0.75" BSPP	0.75" NPT / 0.75" NPT	0.75" NPT / 0.75" NPT
<b>MOUNTING SIZE, &amp; THREAD, TYPE</b>	Foot Mount / Portable Carry Handle	Foot Mount / Portable Carry Handle	Foot Mount / Portable Carry Handle	2" NPT Bung Mount
<b>KEY INCLUDED COMPONENTS</b>	Power Cord with Battery Clips	Power Cord with Battery Clips	¾" x 8' Hose with Static Wire, ¾" x 6' Suction Hose with Static Wire, ¾" Cast Aluminum Manual Nozzle, Power Cord with Battery Clips	¾" x 8' Hose with Static Wire, ¾" Cast Aluminum Manual Nozzle, 23" – 40" Polypropylene Telescoping Suction Pipe, Power Cord with Battery Clips, 2" x 1" x ¾" Double Tap Bushing
<b>COMPATIBLE FLUIDS</b>				
<b>PACKAGE DIMENSIONS (WxHxD) / WEIGHT</b>	8.88" x 7.25" x 8.88" / 10.5 lbs	8.88" x 7.25" x 8.88" / 10.5 lbs	17.88" x 7.25" x 17.88" / 19 lbs	17.88" x 7.25" x 17.88" / 17.9 lbs
<b>CERTIFICATIONS</b>	ATEX, CE, cULus, IECEX	ATEX, CE, cULus, IECEX	ATEX, CE, cULus, IECEX	ATEX, CE, cULus, IECEX
<b>WARRANTY</b>	2 Years	2 Years	2 Years	2 Years
<b>UPC</b>	089404224717	089404225080	089404225066	089404225073

DC PUMPS

AC PUMPS

NEXT-EC

HAND PUMPS

METERS

CABINET DISPENSERS

FMS

ACCESSORIES

DEF

KITS