

RD812NN



RD812NH



RD812NP



RD1212NN



DESCRIPTION	Pump Only	Suction Hose, Manual Nozzle	Suction Pipe, Manual Nozzle	Pump Only
FLOW RATE	8 GPM / 30 LPM	8 GPM / 30 LPM	8 GPM / 30 LPM	12 GPM / 45 LPM
VOLTAGE / AMP RATING (FLA)	12V DC / 14 A	12V DC / 14 A	12V DC / 14 A	12V DC / 14 A
DUTY CYCLE	30 min on / 30 min off	30 min on / 30 min off	30 min on / 30 min off	30 min on / 30 min off
DISCHARGE HEAD / DISCHARGE PRESSURE	37' / 16 PSI	37' / 16 PSI	37' / 16 PSI	37' / 16 PSI
SUCTION LIFT (FT)	6'	6'	6'	6'
INLET THREAD / OUTLET THREAD	0.75" NPT / 0.75" NPT	0.75" NPT / 0.75" NPT	0.75" NPT / 0.75" NPT	0.75" NPT / 0.75" NPT
MOUNTING SIZE, THREAD, TYPE	Portable Carry Handle	Portable Carry Handle	2" Bung Mount	Foot Mount / Portable Carry Handle
KEY INCLUDED COMPONENTS	Power Cord with Battery Clips	5/8" x 8' UL Listed Hose with Static Ground Wire, 3/4" x 6' Suction Hose with Static Wire, 3/4" Cast Aluminum Manual Nozzle, Power Cord with Battery Slips	5/8" x 8' UL Listed Hose with Static Ground Wire, 3/4" Cast Aluminum Manual Nozzle, 23" - 40" Polypropylene Telescoping Suction Pipe, Power cord with Battery Clips, 2" x 1" x 3/4" Double Tap Bushing	Power Cord with Battery Clips
COMPATIBLE FLUIDS				
PACKAGE DIMENSIONS (WxHxD) / WEIGHT	8.88" x 7.25" x 8.88" / 10 lbs	17.88" x 7.25" x 17.88" / 18 lbs	17.88" x 7.25" x 17.88" / 18 lbs	8.88" x 7.25" x 8.88" / 9.5 lbs
CERTIFICATIONS	ATEX, CE, cULus, IECEX	ATEX, CE, cULus, IECEX	ATEX, CE, cULus, IECEX	ATEX, CE, cULus, IECEX
WARRANTY	2 Years	2 Years	2 Years	2 Years
UPC	089404224687	089404224700	089404224694	089404225059