



AQUAPROOF™

- 30 mil thick grey PVC shower pan liner marked every 6" for easy cutting
- Creates permanent waterproofing under tile, concrete, etc.
- Meets ASTM D 4551, cUPC listed, IPC & IRC Compliant

Product Code #	Product Description	UPC Barcode	Units/Case	Lbs/Case
AQ430	4' x 50' (1.2 m x 15.2 m) Roll - 200 sq ft	0 67001-00019 4	1	46
AQ530	5' x 40' (1.5 m x 12.2 m) Roll - 200 sq ft	0 67001-00020 0	1	46
AQ630	6' x 33.3' (1.8 m x 10.1 m) Roll - 200 sq ft	0 67001-00152 8	1	46



SOLVENT CEMENT (for joining PVC to PVC)

AQS	500 ml (1 pt) Can with Applicator Cap	0 67001-00006 4	12	15
-----	---------------------------------------	-----------------	----	----

CONTACT CEMENT (for joining PVC to subfloor)

CC 24	950 ml (1 qt) Can	0 58751-24100 5	6	20
-------	-------------------	-----------------	---	----



LEAK DETECTOR

- Bubble type non-freezing (to -35°F/-37°C) liquid quickly locates pin hole leaks even at low pressures
- Will detect leaks of various gases in appliances, air & gas lines, cylinders, pipe & fittings, pressure vessels, tanks, tubing and valves
- Not for use on oxygen systems
- Available in clear or pink liquid

Product Code #	Product Description	UPC Barcode	Units/Case	Lbs/Case
LD059	59 ml (1/8 pt) Spray Bottle	0 67001-00059 0	20	5
LD227	227 ml (1/2 pt) Applicator Bottle	0 67001-00012 5	20	13
LD500	500 ml (1 pt) Spray Bottle	0 67001-00165 8	12	15
LD4L	4 L (1 gal) Jug	0 67001-00018 7	4	34
LD20L	20 L (5 gal) Pail	0 67001-00052 1	1	44



CUTTING OIL

- Heavy duty sulphurized, paraffinic oil specially blended for pipe threading, tapping, drilling, milling, broaching and general machine use
- Recommended for use on high carbon and alloy steels, stainless steel, many ferrous and non-ferrous metals as well as aluminum

Product Code #	Product Description	UPC Barcode	Units/Case	Lbs/Case
CO500	500 ml (1 pt) Spray Bottle	0 67001-00196 2	12	14
CO1L	1 L (1 qt) Pour Spout Bottle	0 67001-00048 4	12	27
CO4L	4 L (1 gal) Jug	0 67001-00049 1	4	32
CO20L	20 L (5 gal) Pail	0 67001-00050 7	1	42
CO205L	205 L (45 gal) Drum	0 67001-00051 4	1	450

