

PRO-DOPE®

PTFE PIPE THREAD SEALANT

MASTERS® PRO-DOPE® is a non-toxic, non-corrosive, non-hardening paste. It effectively seals both metal and plastic threaded connections. It will not dry out, stain, harden or separate. Lubricates during assembly and can easily be disassembled even after years of service.

MASTERS® PRO-DOPE® effectively seals most liquids and gases against leakage to 10,000 psi and from -200°F to +400°F $(-129^{\circ}\text{C to } + 204^{\circ}\text{C}).$

Directions:

- Stir Well
- Do NOT dilute
- Threads must be clean
- Apply to male threads beginning at 2nd thread

CFIA "Letter of No Objection" **Available**











THE PROPERTY OF THE PARTY OF TH

Gasoline • Natural Gas • Pr

ipe Thread Sealant

Scellant de filets

de conduite

340 g

Listed by Underwriter's Laboratories of Canada and the U.S.

Steam

Sugar (liquid)

Recommended For:

- Acids (dilute)
- · Air (compressed, gaseous)
- Aliphatic Solvents
- Alkalis (dilute)
- Ammonia
- Brine
- Carbon Dioxide

- Castor Oils
- Caustic Alkali (dilute)
- Corrosives
- Diesel Fuel Oil
- Gasoline
- Heating Oils
- · Helium (gaseous)
- Hydraulic Oils
- Inert Gases (gaseous)
- Jet Fuel (JP4,5 & 6)
- Kerosene
- Liquified Petroleum Gases
- Manufactured Gases
- Mineral Oils

- Natural Gas
- Nitrogen (gaseous)
- Oils
- Petroleum Solvents
- Potable Water
- Propane
- Refrigerants (most)

Catalogue Number	Description	Quantity Per Case	Approximate Case Shipping Weight	
PD250BT	250 ml (1/2 pt) Brush-Top Can	25	26.7 lbs	12.1 kg
PD500BT	500 ml (1 pt) Brush-Top Can	12	22.9 lbs	10.4 kg
PD1L	1L (1 qt) Flat-Top Can	4	13.3 lbs	6.0 kg
PD20L	20 L (5 gal) Pail	1	58.0 lbs	26.3 kg

For full chemical compatibility, contact us directly. Exercise caution when working with chemicals with low surface tension. Not safe for use on oxygen systems.

















Find us on









