



YELLOW T-TAPE GAS SEAL TAPE

MASTERS® YELLOW T-TAPE seals all metal and plastic threaded connections against leakage at temperatures from -400°F to +600°F (-240°C to +316°C).

MASTERS® YELLOW T-TAPE is non-corrosive, non-flammable, clean, easy to use and is available in a wide range of widths and lengths. Joints disassemble easily, even after years of service. It is coloured yellow for easy identification during inspection.

Because it is chemically inert, MASTERS® YELLOW T-TAPE is impervious to virtually everything including:

- Acids & Alkali
- Air
- Ammonia
- Chlorine
- CO₂
- Fuels
- Gasoline
- Hydrocarbons
- Kerosene
- Natural Gas (ULC Tape Only)
- Nitrogen
- Oxygen
- Refrigerants (most)
- Solvents
- Steam
- Water

Meets MIL SPEC A-A-58092 (superceding T-27730A)



Listed by Underwriter's Laboratories of Canada and the U.S.
For up to 3" pipe.

Directions:

- Make sure threads are clean and remove any shreds of previously applied tape.
- Beginning with the first thread of the male end, wrap tape in the direction of the thread spiral. Use enough for a good seal.
- Tighten the joint using a wrench.

Catalogue Number	Description	Quantity Per Case	Approximate Case Shipping Weight	
TYB480	1/2" x 480" (1.27 cm x 12.19 m) ULC Listed Roll	24	1.9 lbs.	0.9 kg
TYB260V	1/2" x 260" (1.27 cm x 12.19 m) ULC Listed Roll	100	6 lbs.	2.7 kg
TYB480V	1/2" x 480" (1.27 cm x 12.19 m) ULC Listed Roll	100	8 lbs.	3.6 kg



©2020 OateySCS. All Rights Reserved. This information is based on data believed to be reliable but Oatey makes no warranties, express or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties but should not be used to establish specification limits or used alone as the basis of design. Oatey's liability to purchasers is expressly limited to the terms and conditions of sale. Oatey is a trademark of Oatey Co. Oatey Co. is part of the Oatey family of companies. All other trademarks can be found on www.oatey.ca.