

“The Best Hose Suspension in the World”



MODEL
HB 125 ED

For
Hose I.D. 1¹/₄" (3.1cm)



Material:	URETHANE	
Length:	17.5" / 44.45 cm	
Shipping Weight:	3.5 lbs / 1.6 kgs	
Shipping Dimensions:	21 x 8 x 4" / 53.4 x 21 x 10 cm	
Sling Model:	Metal "D-Ring" Sling	
Sling Type:	RS 16D	
*Sling height:	7" / 17.8 cm	
Sling Material:	UV Resistant Treated Polyester	
Rated Capacity:	1350 lbs/ 612 kgs @ 5:1 WLL	437 kgs/ 964 lbs @ 7:1 WLL
Maximum Temperature:	200° F / 93.3° C	

*Measured from top of the bun to the top of the sling

Notes: Used with petroleum hose, refueling stations with hyhose retractors, hydraulic hose bundles and theatrical cabling.

CE certified slings available at a rated capacity of 500 kgs @ 7:1



© 2015 property of IceCap Equity Corp. All Rights Reserved.

USA & Canada (Toll Free)

Tel: 888-829-3773

Fax: 877-382-9626

International

Tel: 403-294-0275

Fax: 403-294-0274

Email: info@hosebun.com