

Product Update Notification

Mag-FLEX Tall Tank Probe – Extended Sizes & Additional Temperature Sensors

Overview

The Veeder-Root Magnetostrictive Mag-FLEX Tall Tank Probe sizes have been extended to now monitor taller tanks. The maximum probe length was 49 feet/15 meters and is now 72 feet/22 meters. Additional temperature sensors have also been added to all probe lengths for improved temperature accuracy. This enhanced product, paired with any Veeder-Root Automatic Tank Gauge (ATG), delivers accurate reconciliation of your most expensive on-site assets, while eliminating the safety hazard of scaling formidable heights to determine inventory levels of Aboveground Storage Tanks (ASTs).



Product Specifications

PRODUCT MEASUREMENT		
Height Accuracy	±0.08" (±0.2cm)	
Repeatability	±0.02" (±0.05cm)	
Minimum Product Level Reading	7.3" (18.5cm)	
Float Size	1.7" (4.3cm)	
WATER MEASUREMENT		
	Standard	Optional
Height Accuracy	±0.12" (±0.3cm)	±0.12" (±0.3cm)
Repeatability	±0.02" (±0.05cm)	±0.02" (±0.05cm)
Minimum Water Level Reading	5.5" (14cm)	1.9" (4.8cm)
Float Size	1.7" (4.3cm)	4" (10.2cm)
TEMPERATURE MEASUREMENT		
Operating Range	-40°F to 140°F (-40°C to 60°C)	
Accuracy	±0.36°F (±0.2°C) @ -40°F (-40°C) to 185°F (85°C) ±0.18°F (±0.1°C) @ -4°F (-20°C) to 131°F (55°C)	
Repeatability	±0.5°F (±0.5°C)	
Resolution	0.1°F (0.1°C)	
Thermistors	5 Thermistors	
INSTALLATION DETAILS		
Probe Shaft Length	Up to 72' (22m) tank height	
Tank Adapter/Tank Entry	R 1.5" (3.8cm) screw-in unit	
Height Adjustment Range	±9.8" (24.9cm)	
Electrical Connection	M12 plug-in connection	
Protection Class	IP68	
SENSOR MATERIALS		
Probe Canister	Stainless steel 303	
Rigid Shaft Sections	Stainless steel 304	
Corrugated Flexible Shaft & Floats	Stainless steel 316 Ti	
Weight	Stainless steel 303	
Magnet Casing	Conductive plastic	
GENERAL INFORMATION		
Options	Tank adapter made of stainless steel. Weight made of stainless steel.	
Certifications	ATEX, IECEx, UL, cUL	

FEATURES & BENEFITS

- **Single point of monitoring** – Automate product level, water level and temperature monitoring of storage tanks with a Veeder-Root fuel monitoring system.
- **Water detection** – The standard water float included detects water at the 5.5" (14cm) level. An optional low-level water float is also available for water detection at the 1.9" (4.8cm) level, which requires a 4" (10.2cm) tank opening.
- **Wireless & Wired applications** – Save installation time and cost with wireless technology, which eliminates wiring from the tank to the ATG. Where wireless is not practical, Mag-FLEX accommodates traditional wired installation as well.
- **Scalable solution to various site profiles** – The Veeder-Root ATG portfolio offers a wide range of consoles to best suit various site configurations.
- **Flexible, corrugated probe design** – Provides for easy transportation and installation.
- **Stainless steel probe shaft** – Provides increased protection of the mag wire and probe durability.

► Console Compatibility

WIRED VERSION				
Part Number	Console Type	Software Version	Tank Capacity	
			Gallons	Liters
08895x1-4xx, 5xx and 6xx	TLS-450PLUS	6A	264,172,052	999,999,999
	TLS4 / TLS4B	6A		
WIRELESS VERSION				
Part Number	Console Type	Software Version	Tank Capacity	
			Gallons	Liters
08895x1-1xx, 2xx and 3xx	TLS-450PLUS	5B	264,172,052	999,999,999
	TLS4 / TLS4B	5B		
	TLS-350 Series	22	999,999	3,784,996
	TLS-300 Series	22		

Note: Liters may be increased by programming in English units first and switching the console to Metric units.

► Ordering Information

Mag-FLEX Tall Tank Probes are supplied as a complete assembly under a single part number that includes the following items:

- Flexible magnetostrictive probe
- Product float
- Integral stainless steel weight and magnetic base
- Probe leader cable (6ft/1.8m)
- Water float, if applicable
- Wall guide included in low level float kit, if applicable

Mag-FLEX Wireless: Mag-FLEX probes are fully compatible with Veeder-Root TLS-RF Wireless 2 systems.

Purchase Order Requirements: All purchase orders must be submitted with a completed Mag-FLEX order entry worksheet. The order entry worksheet can be obtained by contacting Customer Service.

Note: New part numbers are replacing the existing Mag-Flex Probe part numbers. Refer to the list attached to this notification for details.

Support

- ☎ **+1.814.695.4476** – Customer Service (International)
- ☎ **+1.800.873.3313** – Customer Service
- ☎ **+1.800.323.1799** – Technical Support
- 📄 **+1.800.234.5350** – Customer Service
- ✉ customerservice@veeder.com



Mag-FLEX Probes with Water and Product Floats for Gasoline Tanks – Wired, UL/cUL		
Old Part Number	New Part Number	Description
0889590-400	0889591-400	Mag-FLEX probe, gasoline float (5.0 to 6.5'), wired, UL/cUL
0889590-401	0889591-401	Mag-FLEX probe, gasoline float (6.6 to 9.8'), wired, UL/cUL
0889590-402	0889591-402	Mag-FLEX probe, gasoline float (9.9 to 13.1'), wired, UL/cUL
0889590-403	0889591-403	Mag-FLEX probe, gasoline float (13.2 to 16.4'), wired, UL/cUL
0889590-404	0889591-404	Mag-FLEX probe, gasoline float (16.5 to 19.6'), wired, UL/cUL
0889590-405	0889591-405	Mag-FLEX probe, gasoline float (19.7 to 22.9'), wired, UL/cUL
0889590-406	0889591-406	Mag-FLEX probe, gasoline float (23.0 to 26.2'), wired, UL/cUL
0889590-407	0889591-407	Mag-FLEX probe, gasoline float (26.3 to 29.5'), wired, UL/cUL
0889590-408	0889591-408	Mag-FLEX probe, gasoline float (29.6 to 32.8'), wired, UL/cUL
0889590-409	0889591-409	Mag-FLEX probe, gasoline float (32.9 to 36.0'), wired, UL/cUL
0889590-410	0889591-410	Mag-FLEX probe, gasoline float (36.1 to 39.3'), wired, UL/cUL
0889590-411	0889591-411	Mag-FLEX probe, gasoline float (39.4 to 42.6'), wired, UL/cUL
0889590-412	0889591-412	Mag-FLEX probe, gasoline float (42.7 to 45.9'), wired, UL/cUL
0889590-413	0889591-413	Mag-FLEX probe, gasoline float (46.0 to 49.2'), wired, UL/cUL
X	0889591-414	Mag-FLEX probe, gasoline float (49.3 to 52.5'), wired, UL/cUL
X	0889591-415	Mag-FLEX probe, gasoline float (52.6 to 55.7'), wired, UL/cUL
X	0889591-416	Mag-FLEX probe, gasoline float (55.8 to 59'), wired, UL/cUL
X	0889591-417	Mag-FLEX probe, gasoline float (59.1 to 62.3'), wired, UL/cUL
X	0889591-418	Mag-FLEX probe, gasoline float (62.4 to 65.6'), wired, UL/cUL
X	0889591-419	Mag-FLEX probe, gasoline float (65.7 to 68.8'), wired, UL/cUL
X	0889591-420	Mag-FLEX probe, gasoline float (68.9 to 72.1'), wired, UL/cUL

Mag-FLEX Probes with Water and Product Floats for Diesel Tanks – Wired, UL/cUL		
Old Part Number	New Part Number	Description
0889590-500	0889591-500	Mag-FLEX probe, diesel float (5.0 to 6.5'), wired, UL/cUL
0889590-501	0889591-501	Mag-FLEX probe, diesel float (6.6 to 9.8'), wired, UL/cUL
0889590-502	0889591-502	Mag-FLEX probe, diesel float (9.9 to 13.1'), wired, UL/cUL
0889590-503	0889591-503	Mag-FLEX probe, diesel float (13.2 to 16.4'), wired, UL/cUL
0889590-504	0889591-504	Mag-FLEX probe, diesel float (16.5 to 19.6'), wired, UL/cUL
0889590-505	0889591-505	Mag-FLEX probe, diesel float (19.7 to 22.9'), wired, UL/cUL
0889590-506	0889591-506	Mag-FLEX probe, diesel float (23.0 to 26.2'), wired, UL/cUL
0889590-507	0889591-507	Mag-FLEX probe, diesel float (26.3 to 29.5'), wired, UL/cUL
0889590-508	0889591-508	Mag-FLEX probe, diesel float (29.6 to 32.8'), wired, UL/cUL
0889590-509	0889591-509	Mag-FLEX probe, diesel float (32.9 to 36.0'), wired, UL/cUL
0889590-510	0889591-510	Mag-FLEX probe, diesel float (36.1 to 39.3'), wired, UL/cUL
0889590-511	0889591-511	Mag-FLEX probe, diesel float (39.4 to 42.6'), wired, UL/cUL
0889590-512	0889591-512	Mag-FLEX probe, diesel float (42.7 to 45.9'), wired, UL/cUL
0889590-513	0889591-513	Mag-FLEX probe, diesel float (46.0 to 49.2'), wired, UL/cUL
X	0889591-514	Mag-FLEX probe, diesel float (49.3 to 52.5'), wired, UL/cUL
X	0889591-515	Mag-FLEX probe, diesel float (52.6 to 55.7'), wired, UL/cUL
X	0889591-516	Mag-FLEX probe, diesel float (55.8 to 59'), wired, UL/cUL
X	0889591-517	Mag-FLEX probe, diesel float (59.1 to 62.3'), wired, UL/cUL
X	0889591-518	Mag-FLEX probe, diesel float (62.4 to 65.6'), wired, UL/cUL
X	0889591-519	Mag-FLEX probe, diesel float (65.7 to 68.8'), wired, UL/cUL
X	0889591-520	Mag-FLEX probe, diesel float (68.9 to 72.1'), wired, UL/cUL

Mag-FLEX Probes with No Water Detection Float – Wired, UL/cUL		
Old Part Number	New Part Number	Description
0889590-600	0889591-600	Mag-FLEX probe, no water float (5.0 to 6.5'), wired, UL/cUL
0889590-601	0889591-601	Mag-FLEX probe, no water float (6.6 to 9.8'), wired, UL/cUL
0889590-602	0889591-602	Mag-FLEX probe, no water float (9.9 to 13.1'), wired, UL/cUL
0889590-603	0889591-603	Mag-FLEX probe, no water float (13.2 to 16.4'), wired, UL/cUL
0889590-604	0889591-604	Mag-FLEX probe, no water float (16.5 to 19.6'), wired, UL/cUL
0889590-605	0889591-605	Mag-FLEX probe, no water float (19.7 to 22.9'), wired, UL/cUL
0889590-606	0889591-606	Mag-FLEX probe, no water float (23.0 to 26.2'), wired, UL/cUL
0889590-607	0889591-607	Mag-FLEX probe, no water float (26.3 to 29.5'), wired, UL/cUL
0889590-608	0889591-608	Mag-FLEX probe, no water float (29.6 to 32.8'), wired, UL/cUL
0889590-609	0889591-609	Mag-FLEX probe, no water float (32.9 to 36.0'), wired, UL/cUL
0889590-610	0889591-610	Mag-FLEX probe, no water float (36.1 to 39.3'), wired, UL/cUL
0889590-611	0889591-611	Mag-FLEX probe, no water float (39.4 to 42.6'), wired, UL/cUL
0889590-612	0889591-612	Mag-FLEX probe, no water float (42.7 to 45.9'), wired, UL/cUL
0889590-613	0889591-613	Mag-FLEX probe, no water float (46.0 to 49.2'), wired, UL/cUL
X	0889591-614	Mag-FLEX probe, no water float (49.3 to 52.5'), wired, UL/cUL
X	0889591-615	Mag-FLEX probe, no water float (52.6 to 55.7'), wired, UL/cUL
X	0889591-616	Mag-FLEX probe, no water float (55.8 to 59'), wired, UL/cUL
X	0889591-617	Mag-FLEX probe, no water float (59.1 to 62.3'), wired, UL/cUL
X	0889591-618	Mag-FLEX probe, no water float (62.4 to 65.6'), wired, UL/cUL
X	0889591-619	Mag-FLEX probe, no water float (65.7 to 68.8'), wired, UL/cUL
X	0889591-620	Mag-FLEX probe, no water float (68.9 to 72.1'), wired, UL/cUL

Mag-FLEX Probes with Water and Product Floats for Gasoline Tanks – Wireless, UL/cUL		
Old Part Number	New Part Number	Description
0889590-100	0889591-100	Mag-FLEX probe, gasoline float (5.0 to 6.5'), wireless, UL/cUL
0889590-101	0889591-101	Mag-FLEX probe, gasoline float (6.6 to 9.8'), wireless, UL/cUL
0889590-102	0889591-102	Mag-FLEX probe, gasoline float (9.9 to 13.1'), wireless, UL/cUL
0889590-103	0889591-103	Mag-FLEX probe, gasoline float (13.2 to 16.4'), wireless, UL/cUL
0889590-104	0889591-104	Mag-FLEX probe, gasoline float (16.5 to 19.6'), wireless, UL/cUL
0889590-105	0889591-105	Mag-FLEX probe, gasoline float (19.7 to 22.9'), wireless, UL/cUL
0889590-106	0889591-106	Mag-FLEX probe, gasoline float (23.0 to 26.2'), wireless, UL/cUL
0889590-107	0889591-107	Mag-FLEX probe, gasoline float (26.3 to 29.5'), wireless, UL/cUL
0889590-108	0889591-108	Mag-FLEX probe, gasoline float (29.6 to 32.8'), wireless, UL/cUL
0889590-109	0889591-109	Mag-FLEX probe, gasoline float (32.9 to 36.0'), wireless, UL/cUL
0889590-110	0889591-110	Mag-FLEX probe, gasoline float (36.1 to 39.3'), wireless, UL/cUL
0889590-111	0889591-111	Mag-FLEX probe, gasoline float (39.4 to 42.6'), wireless, UL/cUL
0889590-112	0889591-112	Mag-FLEX probe, gasoline float (42.7 to 45.9'), wireless, UL/cUL
0889590-113	0889591-113	Mag-FLEX probe, gasoline float (46.0 to 49.2'), wireless, UL/cUL
X	0889591-114	Mag-FLEX probe, gasoline float (49.3 to 52.5'), wireless, UL/cUL
X	0889591-115	Mag-FLEX probe, gasoline float (52.6 to 55.7'), wireless, UL/cUL
X	0889591-116	Mag-FLEX probe, gasoline float (55.8 to 59'), wireless, UL/cUL
X	0889591-117	Mag-FLEX probe, gasoline float (59.1 to 62.3'), wireless, UL/cUL
X	0889591-118	Mag-FLEX probe, gasoline float (62.4 to 65.6'), wireless, UL/cUL
X	0889591-119	Mag-FLEX probe, gasoline float (65.7 to 68.8'), wireless, UL/cUL
X	0889591-120	Mag-FLEX probe, gasoline float (68.9 to 72.1'), wireless, UL/cUL

Mag-FLEX Probes with Water and Product Floats for Diesel Tanks – Wireless, UL/cUL		
Old Part Number	New Part Number	Description
0889590-200	0889591-200	Mag-FLEX probe, diesel float (5.0 to 6.5'), wireless, UL/cUL
0889590-201	0889591-201	Mag-FLEX probe, diesel float (6.6 to 9.8'), wireless, UL/cUL
0889590-202	0889591-202	Mag-FLEX probe, diesel float (9.9 to 13.1'), wireless, UL/cUL
0889590-203	0889591-203	Mag-FLEX probe, diesel float (13.2 to 16.4'), wireless, UL/cUL
0889590-204	0889591-204	Mag-FLEX probe, diesel float (16.5 to 19.6'), wireless, UL/cUL
0889590-205	0889591-205	Mag-FLEX probe, diesel float (19.7 to 22.9'), wireless, UL/cUL
0889590-206	0889591-206	Mag-FLEX probe, diesel float (23.0 to 26.2'), wireless, UL/cUL
0889590-207	0889591-207	Mag-FLEX probe, diesel float (26.3 to 29.5'), wireless, UL/cUL
0889590-208	0889591-208	Mag-FLEX probe, diesel float (29.6 to 32.8'), wireless, UL/cUL
0889590-209	0889591-209	Mag-FLEX probe, diesel float (32.9 to 36.0'), wireless, UL/cUL
0889590-210	0889591-210	Mag-FLEX probe, diesel float (36.1 to 39.3'), wireless, UL/cUL
0889590-211	0889591-211	Mag-FLEX probe, diesel float (39.4 to 42.6'), wireless, UL/cUL
0889590-212	0889591-212	Mag-FLEX probe, diesel float (42.7 to 45.9'), wireless, UL/cUL
0889590-213	0889591-213	Mag-FLEX probe, diesel float (46.0 to 49.2'), wireless, UL/cUL
X	0889591-214	Mag-FLEX probe, diesel float (49.3 to 52.5'), wireless, UL/cUL
X	0889591-215	Mag-FLEX probe, diesel float (52.6 to 55.7'), wireless, UL/cUL
X	0889591-216	Mag-FLEX probe, diesel float (55.8 to 59'), wireless, UL/cUL
X	0889591-217	Mag-FLEX probe, diesel float (59.1 to 62.3'), wireless, UL/cUL
X	0889591-218	Mag-FLEX probe, diesel float (62.4 to 65.6'), wireless, UL/cUL
X	0889591-219	Mag-FLEX probe, diesel float (65.7 to 68.8'), wireless, UL/cUL
X	0889591-220	Mag-FLEX probe, diesel float (68.9 to 72.1'), wireless, UL/cUL

Mag-FLEX Probes with Product Float and No Water Detection Float – Wireless, UL/cUL		
Old Part Number	New Part Number	Description
0889590-300	0889591-300	Mag-FLEX probe, no water float (5.0 to 6.5'), wireless, UL/cUL
0889590-301	0889591-301	Mag-FLEX probe, no water float (6.6 to 9.8'), wireless, UL/cUL
0889590-302	0889591-302	Mag-FLEX probe, no water float (9.9 to 13.1'), wireless, UL/cUL
0889590-303	0889591-303	Mag-FLEX probe, no water float (13.2 to 16.4'), wireless, UL/cUL
0889590-304	0889591-304	Mag-FLEX probe, no water float (16.5 to 19.6'), wireless, UL/cUL
0889590-305	0889591-305	Mag-FLEX probe, no water float (19.7 to 22.9'), wireless, UL/cUL
0889590-306	0889591-306	Mag-FLEX probe, no water float (23.0 to 26.2'), wireless, UL/cUL
0889590-307	0889591-307	Mag-FLEX probe, no water float (26.3 to 29.5'), wireless, UL/cUL
0889590-308	0889591-308	Mag-FLEX probe, no water float (29.6 to 32.8'), wireless, UL/cUL
0889590-309	0889591-309	Mag-FLEX probe, no water float (32.9 to 36.0'), wireless, UL/cUL
0889590-310	0889591-310	Mag-FLEX probe, no water float (36.1 to 39.3'), wireless, UL/cUL
0889590-311	0889591-311	Mag-FLEX probe, no water float (39.4 to 42.6'), wireless, UL/cUL
0889590-312	0889591-312	Mag-FLEX probe, no water float (42.7 to 45.9'), wireless, UL/cUL
0889590-313	0889591-313	Mag-FLEX probe, no water float (46.0 to 49.2'), wireless, UL/cUL
X	0889591-314	Mag-FLEX probe, no water float (49.3 to 52.5'), wireless, UL/cUL
X	0889591-315	Mag-FLEX probe, no water float (52.6 to 55.7'), wireless, UL/cUL
X	0889591-316	Mag-FLEX probe, no water float (55.8 to 59'), wireless, UL/cUL
X	0889591-317	Mag-FLEX probe, no water float (59.1 to 62.3'), wireless, UL/cUL
X	0889591-318	Mag-FLEX probe, no water float (62.4 to 65.6'), wireless, UL/cUL
X	0889591-319	Mag-FLEX probe, no water float (65.7 to 68.8'), wireless, UL/cUL
X	0889591-320	Mag-FLEX probe, no water float (68.9 to 72.1'), wireless, UL/cUL

Mag-FLEX Probes with Water and Product Floats for Gasoline Tanks – Wired, ATEX		
Old Part Number	New Part Number	Description
0889560-400	0889561-400	Mag-FLEX probe, gasoline float (5.0 to 6.5'), wired, ATEX
0889560-401	0889561-401	Mag-FLEX probe, gasoline float (6.6 to 9.8'), wired, ATEX
0889560-402	0889561-402	Mag-FLEX probe, gasoline float (9.9 to 13.1'), wired, ATEX
0889560-403	0889561-403	Mag-FLEX probe, gasoline float (13.2 to 16.4'), wired, ATEX
0889560-404	0889561-404	Mag-FLEX probe, gasoline float (16.5 to 19.6'), wired, ATEX
0889560-405	0889561-405	Mag-FLEX probe, gasoline float (19.7 to 22.9'), wired, ATEX
0889560-406	0889561-406	Mag-FLEX probe, gasoline float (23.0 to 26.2'), wired, ATEX
0889560-407	0889561-407	Mag-FLEX probe, gasoline float (26.3 to 29.5'), wired, ATEX
0889560-408	0889561-408	Mag-FLEX probe, gasoline float (29.6 to 32.8'), wired, ATEX
0889560-409	0889561-409	Mag-FLEX probe, gasoline float (32.9 to 36.0'), wired, ATEX
0889560-410	0889561-410	Mag-FLEX probe, gasoline float (36.1 to 39.3'), wired, ATEX
0889560-411	0889561-411	Mag-FLEX probe, gasoline float (39.4 to 42.6'), wired, ATEX
0889560-412	0889561-412	Mag-FLEX probe, gasoline float (42.7 to 45.9'), wired, ATEX
0889560-413	0889561-413	Mag-FLEX probe, gasoline float (46.0 to 49.2'), wired, ATEX
X	0889561-414	Mag-FLEX probe, gasoline float (49.3 to 52.5'), wired, ATEX
X	0889561-415	Mag-FLEX probe, gasoline float (52.6 to 55.7'), wired, ATEX
X	0889561-416	Mag-FLEX probe, gasoline float (55.8 to 59'), wired, ATEX
X	0889561-417	Mag-FLEX probe, gasoline float (59.1 to 62.3'), wired, ATEX
X	0889561-418	Mag-FLEX probe, gasoline float (62.4 to 65.6'), wired, ATEX
X	0889561-419	Mag-FLEX probe, gasoline float (65.7 to 68.8'), wired, ATEX
X	0889561-420	Mag-FLEX probe, gasoline float (68.9 to 72.1'), wired, ATEX

Mag-FLEX Probes with Water and Product Floats for Diesel Tanks – Wired, ATEX		
Old Part Number	New Part Number	Description
0889560-500	0889561-500	Mag-FLEX probe, diesel float (5.0 to 6.5'), wired, ATEX
0889560-501	0889561-501	Mag-FLEX probe, diesel float (6.6 to 9.8'), wired, ATEX
0889560-502	0889561-502	Mag-FLEX probe, diesel float (9.9 to 13.1'), wired, ATEX
0889560-503	0889561-503	Mag-FLEX probe, diesel float (13.2 to 16.4'), wired, ATEX
0889560-504	0889561-504	Mag-FLEX probe, diesel float (16.5 to 19.6'), wired, ATEX
0889560-505	0889561-505	Mag-FLEX probe, diesel float (19.7 to 22.9'), wired, ATEX
0889560-506	0889561-506	Mag-FLEX probe, diesel float (23.0 to 26.2'), wired, ATEX
0889560-507	0889561-507	Mag-FLEX probe, diesel float (26.3 to 29.5'), wired, ATEX
0889560-508	0889561-508	Mag-FLEX probe, diesel float (29.6 to 32.8'), wired, ATEX
0889560-509	0889561-509	Mag-FLEX probe, diesel float (32.9 to 36.0'), wired, ATEX
0889560-510	0889561-510	Mag-FLEX probe, diesel float (36.1 to 39.3'), wired, ATEX
0889560-511	0889561-511	Mag-FLEX probe, diesel float (39.4 to 42.6'), wired, ATEX
0889560-512	0889561-512	Mag-FLEX probe, diesel float (42.7 to 45.9'), wired, ATEX
0889560-513	0889561-513	Mag-FLEX probe, diesel float (46.0 to 49.2'), wired, ATEX
X	0889561-514	Mag-FLEX probe, diesel float (49.3 to 52.5'), wired, ATEX
X	0889561-515	Mag-FLEX probe, diesel float (52.6 to 55.7'), wired, ATEX
X	0889561-516	Mag-FLEX probe, diesel float (55.8 to 59'), wired, ATEX
X	0889561-517	Mag-FLEX probe, diesel float (59.1 to 62.3'), wired, ATEX
X	0889561-518	Mag-FLEX probe, diesel float (62.4 to 65.6'), wired, ATEX
X	0889561-519	Mag-FLEX probe, diesel float (65.7 to 68.8'), wired, ATEX
X	0889561-520	Mag-FLEX probe, diesel float (68.9 to 72.1'), wired, ATEX

Mag-FLEX Probes with No Water Detection Float – Wired, ATEX		
Old Part Number	New Part Number	Description
0889560-600	0889561-600	Mag-FLEX probe, no water float (5.0 to 6.5'), wired, ATEX
0889560-601	0889561-601	Mag-FLEX probe, no water float (6.6 to 9.8'), wired, ATEX
0889560-602	0889561-602	Mag-FLEX probe, no water float (9.9 to 13.1'), wired, ATEX
0889560-603	0889561-603	Mag-FLEX probe, no water float (13.2 to 16.4'), wired, ATEX
0889560-604	0889561-604	Mag-FLEX probe, no water float (16.5 to 19.6'), wired, ATEX
0889560-605	0889561-605	Mag-FLEX probe, no water float (19.7 to 22.9'), wired, ATEX
0889560-606	0889561-606	Mag-FLEX probe, no water float (23.0 to 26.2'), wired, ATEX
0889560-607	0889561-607	Mag-FLEX probe, no water float (26.3 to 29.5'), wired, ATEX
0889560-608	0889561-608	Mag-FLEX probe, no water float (29.6 to 32.8'), wired, ATEX
0889560-609	0889561-609	Mag-FLEX probe, no water float (32.9 to 36.0'), wired, ATEX
0889560-610	0889561-610	Mag-FLEX probe, no water float (36.1 to 39.3'), wired, ATEX
0889560-611	0889561-611	Mag-FLEX probe, no water float (39.4 to 42.6'), wired, ATEX
0889560-612	0889561-612	Mag-FLEX probe, no water float (42.7 to 45.9'), wired, ATEX
0889560-613	0889561-613	Mag-FLEX probe, no water float (46.0 to 49.2'), wired, ATEX
X	0889561-614	Mag-FLEX probe, no water float (49.3 to 52.5'), wired, ATEX
X	0889561-615	Mag-FLEX probe, no water float (52.6 to 55.7'), wired, ATEX
X	0889561-616	Mag-FLEX probe, no water float (55.8 to 59'), wired, ATEX
X	0889561-617	Mag-FLEX probe, no water float (59.1 to 62.3'), wired, ATEX
X	0889561-618	Mag-FLEX probe, no water float (62.4 to 65.6'), wired, ATEX
X	0889561-619	Mag-FLEX probe, no water float (65.7 to 68.8'), wired, ATEX
X	0889561-620	Mag-FLEX probe, no water float (68.9 to 72.1'), wired, ATEX

Mag-FLEX Probes with Water and Product Floats for Gasoline Tanks – Wireless, ATEX		
Old Part Number	New Part Number	Description
0889560-100	0889561-100	Mag-FLEX probe, gasoline float (5.0 to 6.5'), wireless, ATEX
0889560-101	0889561-101	Mag-FLEX probe, gasoline float (6.6 to 9.8'), wireless, ATEX
0889560-102	0889561-102	Mag-FLEX probe, gasoline float (9.9 to 13.1'), wireless, ATEX
0889560-103	0889561-103	Mag-FLEX probe, gasoline float (13.2 to 16.4'), wireless, ATEX
0889560-104	0889561-104	Mag-FLEX probe, gasoline float (16.5 to 19.6'), wireless, ATEX
0889560-105	0889561-105	Mag-FLEX probe, gasoline float (19.7 to 22.9'), wireless, ATEX
0889560-106	0889561-106	Mag-FLEX probe, gasoline float (23.0 to 26.2'), wireless, ATEX
0889560-107	0889561-107	Mag-FLEX probe, gasoline float (26.3 to 29.5'), wireless, ATEX
0889560-108	0889561-108	Mag-FLEX probe, gasoline float (29.6 to 32.8'), wireless, ATEX
0889560-109	0889561-109	Mag-FLEX probe, gasoline float (32.9 to 36.0'), wireless, ATEX
0889560-110	0889561-110	Mag-FLEX probe, gasoline float (36.1 to 39.3'), wireless, ATEX
0889560-111	0889561-111	Mag-FLEX probe, gasoline float (39.4 to 42.6'), wireless, ATEX
0889560-112	0889561-112	Mag-FLEX probe, gasoline float (42.7 to 45.9'), wireless, ATEX
0889560-113	0889561-113	Mag-FLEX probe, gasoline float (46.0 to 49.2'), wireless, ATEX
X	0889561-114	Mag-FLEX probe, gasoline float (49.3 to 52.5'), wireless, ATEX
X	0889561-115	Mag-FLEX probe, gasoline float (52.6 to 55.7'), wireless, ATEX
X	0889561-116	Mag-FLEX probe, gasoline float (55.8 to 59'), wireless, ATEX
X	0889561-117	Mag-FLEX probe, gasoline float (59.1 to 62.3'), wireless, ATEX
X	0889561-118	Mag-FLEX probe, gasoline float (62.4 to 65.6'), wireless, ATEX
X	0889561-119	Mag-FLEX probe, gasoline float (65.7 to 68.8'), wireless, ATEX
X	0889561-120	Mag-FLEX probe, gasoline float (68.9 to 72.1'), wireless, ATEX

Mag-FLEX Probes with Water and Product Floats for Diesel Tanks – Wireless, ATEX		
Old Part Number	New Part Number	Description
0889560-200	0889561-200	Mag-FLEX probe, diesel float (5.0 to 6.5'), wireless, ATEX
0889560-201	0889561-201	Mag-FLEX probe, diesel float (6.6 to 9.8'), wireless, ATEX
0889560-202	0889561-202	Mag-FLEX probe, diesel float (9.9 to 13.1'), wireless, ATEX
0889560-203	0889561-203	Mag-FLEX probe, diesel float (13.2 to 16.4'), wireless, ATEX
0889560-204	0889561-204	Mag-FLEX probe, diesel float (16.5 to 19.6'), wireless, ATEX
0889560-205	0889561-205	Mag-FLEX probe, diesel float (19.7 to 22.9'), wireless, ATEX
0889560-206	0889561-206	Mag-FLEX probe, diesel float (23.0 to 26.2'), wireless, ATEX
0889560-207	0889561-207	Mag-FLEX probe, diesel float (26.3 to 29.5'), wireless, ATEX
0889560-208	0889561-208	Mag-FLEX probe, diesel float (29.6 to 32.8'), wireless, ATEX
0889560-209	0889561-209	Mag-FLEX probe, diesel float (32.9 to 36.0'), wireless, ATEX
0889560-210	0889561-210	Mag-FLEX probe, diesel float (36.1 to 39.3'), wireless, ATEX
0889560-211	0889561-211	Mag-FLEX probe, diesel float (39.4 to 42.6'), wireless, ATEX
0889560-212	0889561-212	Mag-FLEX probe, diesel float (42.7 to 45.9'), wireless, ATEX
0889560-213	0889561-213	Mag-FLEX probe, diesel float (46.0 to 49.2'), wireless, ATEX
X	0889561-214	Mag-FLEX probe, diesel float (49.3 to 52.5'), wireless, ATEX
X	0889561-215	Mag-FLEX probe, diesel float (52.6 to 55.7'), wireless, ATEX
X	0889561-216	Mag-FLEX probe, diesel float (55.8 to 59'), wireless, ATEX
X	0889561-217	Mag-FLEX probe, diesel float (59.1 to 62.3'), wireless, ATEX
X	0889561-218	Mag-FLEX probe, diesel float (62.4 to 65.6'), wireless, ATEX
X	0889561-219	Mag-FLEX probe, diesel float (65.7 to 68.8'), wireless, ATEX
X	0889561-220	Mag-FLEX probe, diesel float (68.9 to 72.1'), wireless, ATEX

Mag-FLEX Probes with No Water Detection Float – Wireless, ATEX		
Old Part Number	New Part Number	Description
0889560-300	0889561-300	Mag-FLEX probe, no water float (5.0 to 6.5'), wireless, ATEX
0889560-301	0889561-301	Mag-FLEX probe, no water float (6.6 to 9.8'), wireless, ATEX
0889560-302	0889561-302	Mag-FLEX probe, no water float (9.9 to 13.1'), wireless, ATEX
0889560-303	0889561-303	Mag-FLEX probe, no water float (13.2 to 16.4'), wireless, ATEX
0889560-304	0889561-304	Mag-FLEX probe, no water float (16.5 to 19.6'), wireless, ATEX
0889560-305	0889561-305	Mag-FLEX probe, no water float (19.7 to 22.9'), wireless, ATEX
0889560-306	0889561-306	Mag-FLEX probe, no water float (23.0 to 26.2'), wireless, ATEX
0889560-307	0889561-307	Mag-FLEX probe, no water float (26.3 to 29.5'), wireless, ATEX
0889560-308	0889561-308	Mag-FLEX probe, no water float (29.6 to 32.8'), wireless, ATEX
0889560-309	0889561-309	Mag-FLEX probe, no water float (32.9 to 36.0'), wireless, ATEX
0889560-310	0889561-310	Mag-FLEX probe, no water float (36.1 to 39.3'), wireless, ATEX
0889560-311	0889561-311	Mag-FLEX probe, no water float (39.4 to 42.6'), wireless, ATEX
0889560-312	0889561-312	Mag-FLEX probe, no water float (42.7 to 45.9'), wireless, ATEX
0889560-313	0889561-313	Mag-FLEX probe, no water float (46.0 to 49.2'), wireless, ATEX
X	0889561-314	Mag-FLEX probe, no water float (49.3 to 52.5'), wireless, ATEX
X	0889561-315	Mag-FLEX probe, no water float (52.6 to 55.7'), wireless, ATEX
X	0889561-316	Mag-FLEX probe, no water float (55.8 to 59'), wireless, ATEX
X	0889561-317	Mag-FLEX probe, no water float (59.1 to 62.3'), wireless, ATEX
X	0889561-318	Mag-FLEX probe, no water float (62.4 to 65.6'), wireless, ATEX
X	0889561-319	Mag-FLEX probe, no water float (65.7 to 68.8'), wireless, ATEX
X	0889561-320	Mag-FLEX probe, no water float (68.9 to 72.1'), wireless, ATEX